



## Faster positioning, optimised workflow.

### **KAMA CPX 76 and CPX 106**

*Professional positioning system in two formats.*

#### **Applications**

- › Positioning work for hot foil clichés and hologram stamping
- › Positioning of blind embossing stamps on embossing plates and cutting dies
- › Rahmenformat max. bzw. Messbereich für:  
CPX 76: 700 x 855 mm respectively 600 x 785 mm  
CPX 106: 860 x 1,300 mm respectively 800 x 1,100 mm

#### **Highlights**

- › Quick and accurate cliché mounting outside the stamping machine
- › More uptime for the stamping machine
- › Easy to operate: mounting of the cliché in a single step directly into its target position
- › Expansion of the mounting plate is accurately calculated
- › Sheet expansion with printing is taken into account



**Video**  
Positioning on the CPX

### **KAMA Cockpit with Job-Manager**

*Networked workflow for increased productivity.*

#### **Applications**

- › Control station for communication between KAMA machines and a central IT network
- › Job preparation and assembly area
- › Integrated organising system for chases, platens and tools

#### **Highlights**

- › Network integration of the machines for electronic job control (e.g. JDF based)
- › Machine presets via electronic job ticket
- › Feedback to the MIS (Track & Trace)
- › Status display on mobile devices (smartphone etc.)
- › Efficient job preparation based on KAIZEN principles
- › Integrated positioning device CPX 76 (option)



**Video**  
KAMA Cockpit